Good's MILLWORK

Prefit and Premachined Door Schedule

ORDER NUMBER	PAGE NUMBER	DOOR TYPE / #	SPECIES

FRAME OPENING SIZE ____ x ____ x ____
Width Height Thickness

PREFIT DOOR SIZE ____ X ____ X ____

JAMB TYPE:
- ☐ Flat (square) or (colonial)
- ☐ Single Rabbeted
- ☐ Double Rabbeted
- ☐ Kerf

BEVEL STILES
- ☐ NONE ☐ HINGE
- ☐ BOTH ☐ LOCK

Removable stop is inside unless noted

FIRE RATING
- ☐ 20 NP SINGLE
- ☐ 20 NP PAIR
- ☐ 20 PP
- ☐ 45 PP
- ☐ 60 PP
- ☐ 90 PP SINGLE
- ☐ 90 PP PAIR

HINGES

RADIUS ☐ SQUARE ☐

MANUFACTURER NO./TEMPLATE



LENGTH ☐

BACKSET ☐ GAUGE ☐

TOP OF DOOR TO TOP OF HINGE:
- ☐ 1st Hinge
- ☐ 2nd Hinge
- ☐ 3rd Hinge
- ☐ 4th Hinge

LOCK

MANUFACTURER NO.

TEMPLATE NO.

LOCK TYPE: *(check one)*
- Cylindrical: ☐
- Mortise: ☐
- Other: ☐

TOP OF DOOR TO CENTERLINE OF LOCK: ☐

BACKSET: ☐

LATCH PLATE
- ☐ See Template
- ☐ 1-1/8" x 2-1/4"
- ☐ 1" x 2-1/4"
- ☐ 1-1/8" x 7/8"
- ☐ 1" Hole
- ☐ 7/8" Hole

STRIKES
- ☐ 1-1/8" x 2-3/4"
- ☐ 1-1/8" x 2-1/2"
- ☐ 4-7/8" ASA
- ☐ 2 -1/4"

EXIT DEVICE

TOP OF DOOR TO CENTER OF:
- ☐ LOCK
- ☐ FRONT
- ☐ CYLINDER

☐ DEVICE BACKSET

MFG NO & TRIM

TEMPLATE

OTHER HARDWARES/NOTES

GLASS THICKNESS *(if applicable)*
- ☐ 1/8"
- ☐ 1/4"
- ☐ 3/16"
- ☐ 1/2"
- ☐ 5/16"
- ☐ 3/8"
- ☐ OTHER
- ☐ OPEN

TYPE:

Ball Catches

Template #	Location

FLUSH BOLT TEMPLATE

STRIKE -- SIZE: **TYPE:**

TEMPLATE:

DOOR NUMBER	SWING	JAMB DEPTH	DOOR NUMBER	SWING	JAMB DEPTH

TOTAL DOORS



Left Hand -LH | Right Hand -RH | Right Hand outswing -RHOS | Left Hand outswing -LHOS